

Trendfarbe Creamy wall and ceiling paint

MATT

for interior use – drip-inhibited – good hiding power and coverage
Wet-abrasion resistance class 2 in accordance with EN 13300



1. Product properties and field of application

Solvent- and plasticizer-free, with good hiding power and abrasion resistant, water-vapor-permeable emulsion paint for new and renovation coatings, for interior use on e.g. woodchip and embossed wallpaper, gypsum plasterboard, and cement fiber boards, as well as on brickwork, plaster, and concrete. The creamy and drip-inhibited consistency ensures easy and clean application. Its special formula with special functional filler materials and a slightly rough surface significantly lowers the incidence of abrasion marks and glossy areas (the so-called writing effect) when using intensive colors. If they nevertheless appear, they can be easily removed with a moist microfiber towel (Touch-Protect feature).

Color shade

In accordance with the current color card.

GISCODE

BSW20

Density

approx. 1.25 – 1.35 g/cm³

EN 13300	
Wet-abrasion resistance (complies with abrasion resistance in accordance with DIN 53778)	class 2
max. grain size	fine
degree of gloss	matt

Constituent substances

Vinylacetate-ethylene-copolymer-dispersion, titanium dioxide (depending on the shade), inorganic/organic coloured pigments (depending on the shade), calcium carbonate, silicates, polymer extender, water, additives and preservatives (methyl- and benzisothiazolinone).

2. Application

Application techniques

Rolling, brushing spraying

Perfect Spray:

All spraying equipment bearing the Perfect Spray symbol will deliver optimum results if you dilute SCHÖNER WOHNEN Trendfarbe matt with 10% water. More information at www.schoener-wohnen-farbe.com/spruehen.



Application temperature

Do not apply under +5 °C air and object temperature.

Consumption

Approx. 80–125 ml/m² per coating (determine the exact consumption by means of a test application on the object to be coated.).

Dilution

Rolling, brushing: Do not dilute, ready to use.

Tinting/mixing

All color shades can be mixed with one another.

Application information

Stir well before use. First apply a prime coat to high-contrast and absorbent substrates. For intensive colors, several coats may be required to achieve a uniform surface appearance. Application to contiguous surfaces should always be performed in one work step. For intensive colors in highly stressed areas, e.g. stairwells, we recommend using Trendfarbe in silk gloss. Before beginning work, moisten roller and brush with water. First coat the ceiling and then the walls. Start at the window and work with the incident light. First apply SCHÖNER WOHNEN Trendfarbe to corners and edges. Then use the paint roller to apply 2-3 strips, and spread the paint uniformly in transverse directions (once horizontally and once vertically). Subsequently roll over the surface vertically again without applying pressure. Contiguous surfaces should always be coated "wet on wet" without interruption in order to avoid visible lap marks. Remove the masking tape before the paint dries completely.

Drying time (at 20 °C, 65% r. humidity)

After about 6 hours the renovated rooms can again be used or the walls can be recoated. At lower temperatures and/or high humidity, the drying process takes longer.

Substrate preparation

Substrates must be solid, clean, dry, and load-bearing. Follow the instructions to completely remove non-bearing emulsion, oil and enamel paint coatings with, e.g., paint strippers – biodegradable. Completely remove wall coverings, including remains of paste and wall-glue residues. Completely wash or brush lime paints and chalking surfaces. Mechanically remove any non-bearing, mineral coatings. Allow fresh mineral plaster to dry for at least 4 weeks.

Substrates	Priming	Intermediate coat	Top coat
normally absorbent substrates, e.g. old emulsion coatings, synthetic resin render, lime cement, wall coverings (e.g. woodchip wallpaper, embossed wallpaper)	-	In case of high color shade contrast and brilliant, intensive colors: 1x Trendfarbe matt	1-2x Trendfarbe matt
highly and nonuniformly absorbent substrates such as gypsum plaster, gypsum plasterboard, cement fiber boards, brickwork, concrete, matt emulsion coatings, slightly sanding renders	1x Acryl Tiefgrund		

3. After application

Disposal

Only empty containers without residue are to be recycled. Dispose of containers with dried residue as domestic waste or as construction site waste. Deposit containers with residue that has not dried at a collection point for paint wastes. Dispose of liquid paint according to waste code no. 080112 (in accordance with AVV).

Tool cleaning

Immediately after use with soap and water.

Storage/transport

Securely close open paint buckets. Store in a cool and dry place.

Minimum shelf life: see container label

ADR/RID: not a hazardous material – water pollution classification: WGK 1, in accordance with Administrative Regulation on the Classification of Substances Hazardous to Waters

4. Important information

When applying SCHÖNER WOHNEN Trendfarbe matt, the usual protective measures must be taken. Keep out of the reach of children. Do not inhale spray mist. Use the combination filter A2/P2 for spraying. Ensure proper ventilation during application and drying. Avoid eating, drinking and smoking during application work. Upon contact with eyes or skin, immediately rinse thoroughly with water. Ensure that the material cannot enter the sewage system, bodies of water, or the ground.

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE. May produce an allergic reaction. Allergy information at phone no.: 00800 32665500.

Safety data sheet available on request.

EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains max. 1 g/l VOC.

5. General

All information and values are the products of extensive development work and years of practical experience. Our spoken and written technical recommendations, which we prepare to support the buyer or user to the best of our knowledge on the basis of current information, do not constitute a contractual legal relationship. They do not release the buyer from his/her sole responsibility of assessing our products for suitability to the intended purpose. Our general terms and conditions also apply. Upon publication of a new version of this information sheet as a result of new technical developments, all of the information provided above becomes invalid.

Our experts are glad to help with any other questions at phone no. 00800 35834400.

Date: July 2017